



# ASK POWERTECH

**Industrial Electronics, Panel Board Accessories**  
SF NO.226/4, Permalmai, Malaikadu, Agragaram (P.O),  
Pallipalayam, Erode – 638008

## DIGITAL AC AMMETER DATA SHEET

Model: ASK-333A

### 3-PHASE AMMETER

Model:ASK-333A

Parameters	:	3 Phase Amps R,Y,B
Ranges	:	1 A (or) 5A CT Primary Programmable
Accuracy	:	1.0% of FSD
Display	:	14.2mm LED Red
Auxiliary Power Supply	:	80-270Vac @50Hz, 4VA (Optional:10-40 DC 1VA)
Meter Size	:	ABS Plastic Housing for FR Grade Material a)96mm x 96mm x 45mm (Cut out Size:92/92mm)
Input impedance	:	>1M $\Omega$
Operating Temperature	:	10°C to 55° C
Relative humidity	:	0-- 90%.
Features	:	Microcontroller based meters with low VA burden
	:	4 digit three row seven segment display
	:	CT primary range 1A to 50kA AC programmable
	:	CT Secondary range 0.5A to 5A - AC programmable
	:	Password protected
	:	True RMS measurement of parameters
	:	Auto scaling of parameter values
	:	Two switches for easy onsite programming.

(Yours sincerely)

ASK POWERTECH

