



ASK POWERTECH

Industrial Electronics, Panel Board Accessories
SF NO.226/4, Permalmalai, Malaikadu, Agragaram (P.O),
Pallipalayam, Erode – 638008

DIGITAL AC VOLTMETER DATA SHEET

Model: ASK-333V

3-PHASE AC VOLTMETER

Model:ASK-333V

Parameters	:	Voltage Line to Line & Line to Neutral
Ranges	:	0-800Vpp
Accuracy	:	1.0% of FSD
Display	:	14.2mm LED Red
Auxiliary Power Supply	:	80-270Vac @50Hz, 4VA (Optional:10-40 DC 1VA)
Meter Size	:	ABS Plastic Housing for FR Grade Material a)96mm x 96mm x 45mm (Cut out Size:92/92mm)
Input impedance	:	>1MΩ
Operating Temperature	:	10°C to 55° C
Relative humidity	:	0-- 90%.
Features	:	Microcontroller based meters with low VA burden
	:	4 digit three row seven segment display
	:	PT primary range 50V to 500kV AC programmable
	:	PT Secondary 50V to 500V AC programmable
	:	Password protected
	:	True RMS measurement of parameters
	:	Auto scaling of parameter values
	:	Auto/Manual scrolling of parameters
	:	Two switches for easy onsite programming.



ASK POWERTECH